

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

# SAMAN

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

CUSTOMIZABLE TINT BASE

000

14 fl. oz.

## PENETRATING OIL

# PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6

POS-601-16



6 27720 14631 5

# SAMAN



## PENETRATING OIL

601

MIDNIGHT

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

# SAMAN

Victoriaville, Québec,  
Canada G6T 0T6

POS-602-16



6 27720 14632 2

# SAMAN



## PENETRATING OIL

### 602

### FAIRY DUST

### 16 fl. oz.

## PENETRATING OIL

# PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

# SAMAN

Victoriaville, Québec,  
Canada G6T 0T6

POS-603-16



6 27720 14633 9

# SAMAN



## PENETRATING OIL

### 603

### LLAMA

### 16 fl. oz.

## PENETRATING OIL

# PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

604

DRIED MALT

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

# SAMAN

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

# 605

# VINE

# 16 fl. oz.

## PENETRATING OIL

# PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6

POS-606-16



6 27720 14636 0

# SAMAN



## PENETRATING OIL

606

FUR

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

607

TERRACE

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

608

DESERT

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6

POS-609-16



6 27720 14639 1

# SAMAN



## PENETRATING OIL

609

PYRAMID

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

610

SEA SALT

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

611

ROCKY

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

## PENETRATING OIL

UNLOCK AND PROTECT THE TRUE BEAUTY  
OF WOOD GRAIN IN JUST ONE COAT



RICH FINISH



EXCEPTIONAL  
COVERAGE



LOW ODOR



LOW VOC

### FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

**KEEP OUT OF REACH OF CHILDREN.**

**FIRST AID:**

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice. **Eye Contact:** Flush eyes with water. Get medical attention if irritation persists. **Skin Contact:** Wash with soap and water. Get medical attention if irritation persists.

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

Made in Canada

**SAMAN**

Victoriaville, Québec,  
Canada G6T 0T6



# SAMAN



## PENETRATING OIL

612

SAVANNAH

16 fl. oz.

## PENETRATING OIL

### PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- Matte finish
- Protects
- Natural aspect
- Just one coat
- Tint & Seal
- Can be top coated

The SAMAN penetrating oil, with its unique base, gives a rich hue while providing a rustic, natural appearance that can be polished for a satin finish. While also protecting, coloring, and sealing wood surfaces such as furniture, cabinets, doors, moldings, and floors. Once fully dry, can be covered with the SAMAN Top Coat.

**Surface Preparation for Bare Wood:** Sand the bare wood following the wood grain with #120 sandpaper, then with #150 sandpaper. Carefully remove all sanding dust before applying the penetrating oil.

**Surface Preparation if Already Finished:** Remove any existing finish using sandpaper or a paint stripper. If using a paint stripper, follow the stripper's instructions. If sanding, carefully remove all sanding dust before applying the penetrating oil.

**Application:** Shake the contents well before use. Apply with a soft cloth or cotton wick, following the wood grain. Allow to penetrate for 5-10 minutes before wiping off excess.

**Tip:** It is recommended to test the oil in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

**Coverage:** 16 oz size covers up to 100 ft<sup>2</sup>.

**Drying Time:** 6 to 8 hours under normal temperature and humidity conditions.

**Cleaning:** Clean tools with mineral spirits (paint thinner).

VOC: < 250 g/L

For any additional questions, please consult SAM,  
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.