

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

CUSTOMIZABLE TINT BASE

000

14 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.



For any additional questions, please consult SAM,
our conversational chatbot.

FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

301

ANTIQUE

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND PROTECTION IN ONE COAT



ADHERES TO MANY SURFACES



FAST DRYING



LOW VOC FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

304

AMARETTO

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

307

AGED OAK

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

308

DARK CHESTNUT

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND PROTECTION IN ONE COAT



ADHERES TO MANY SURFACES



FAST DRYING



LOW VOC FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

309

WALNUT

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND PROTECTION IN ONE COAT



ADHERES TO MANY SURFACES



FAST DRYING



LOW VOC FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

310

COFFEE

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

311

COCOA

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND PROTECTION IN ONE COAT



ADHERES TO MANY SURFACES



FAST DRYING



LOW VOC FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

314

DARK WALNUT

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

317

CHALK

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

318

EBONY

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND PROTECTION IN ONE COAT



ADHERES TO MANY SURFACES



FAST DRYING



LOW VOC FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

319

PRESTIGE GREY

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm.

For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL, STAIN & POLY

320

CHARCOAL

16 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 16 oz size covers up to 100 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.