

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL STAIN & POLY

CUSTOMIZABLE TINT BASE

000

28 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-301-32



301

ANTIQUÉ

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION OF COLOR AND PROTECTION



COLOR AND PROTECTION IN ONE COAT



ADHERES TO MANY SURFACES



FAST DRYING



LOW VOC FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-304-32



304

AMARETTO

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-307-32



307

AGED OAK

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-308-32



308

DARK CHESTNUT

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-309-32



309

WALNUT

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-310-32



SAMAN



SEAL STAIN & POLY

310

COFFEE

32 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-311-32



311

COCOA

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-314-32



314

DARK WALNUT

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN



SEAL STAIN & POLY

317

CHALK

32 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM,
our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-318-32



318

EBONY

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-319-32



SAMAN



SEAL STAIN & POLY

319

PRESTIGE GREY

32 fl. oz.

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.

SEAL, STAIN & POLY

THE PERFECT COMBINATION
OF COLOR AND PROTECTION



COLOR AND
PROTECTION
IN ONE COAT



ADHERES TO
MANY SURFACES



FAST
DRYING



LOW VOC
FORMULA

CAUTION DO NOT USE ON FLOORS.

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.



WARNING: This product can expose you to chemicals, including Butyl benzyl phthalate, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6

SSP-320-32



320

CHARCOAL

32 fl. oz.

SAMAN



SEAL STAIN & POLY

SEAL, STAIN & POLY

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

- One easy step
 - Without stripping
 - Protects
- Perfect for furniture, moldings, doors and railings

DO NOT APPLY TO FLOORS.

Surface Preparation for Bare Wood: Ensure that the piece to be stained is properly sanded with #150 sandpaper.

Surface Preparation if Already Varnished: Surfaces in good condition that are already varnished should first be washed with SAMAN TSP eco and lightly sanded with #150 sandpaper. Check the adhesion of the old varnish. Perform a finish compatibility test before starting.

Application: Apply a thin coat of SAMAN Seal, Stain & Poly using a natural bristle brush or foam brush, following the direction of the wood grain. To smooth the surface between coats, lightly sand with #220 sandpaper. The color will become darker, and the gloss will increase. For adequate protection, it is recommended to apply a SAMAN TOP COAT.

Tip: It is recommended to test the stain in an inconspicuous area beforehand to determine if the desired color and effect are achieved. Note that the final color will be determined by the natural color of the wood species, which varies from one to another.

Coverage: 32 oz size covers up to 200 ft².

Drying Time: Dry to the touch in 1 hour. To avoid lap marks, make sure the sections being worked on remain wet. If a second coat is necessary, wait 4 hours before application.

Cleaning: Clean tools with warm soapy water.

VOC: < 250 g/L

As the conditions in which the product is used are beyond our control, we can only guarantee that it fully meets our quality standards, and the manufacturer's responsibility, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.



FINISH WITH STYLE.