

WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT



PREMIUM FLOOR GRADE FORMULA



EXCELLENT BUILD BETWEEN COATS



FAST DRYING



LOW ODOR

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.




WARNING: This product can expose you to chemicals, including NMethyl-2-pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN




WATERBASED TOP COAT

FLOOR GRADE

MATTE

1 gal



WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

Surface Preparation: Sand with #120 or #150 grit sandpaper. Do not use steel wool. Vacuum the dust and wipe with a clean, dry cloth.

For Use on Stain: Follow the manufacturer's instructions for applying the stain. Ensure that the surface is completely dry before applying the SAMAN TOP COAT.

For best results, use SAMAN stains.

Preparation of Already Varnished Surfaces: Surfaces must be dry, clean, and free of dust, mold, wax, grease, and moisture. Already varnished surfaces should be washed first with SAMAN TSP eco and lightly sanded with 150-grit sandpaper.

Mixing: Ensure that the product is at room temperature. Stir regularly with a stick during the application.

Application: Apply 2 to 3 even coats following the direction of the wood grain. Sand between each coat with 180-grit sandpaper. After sanding, vacuum the dust and wipe with a clean, damp cloth to remove all residues.

Recommended Applicators: High-quality brush, lint-free 6mm roller, HVLP spray gun.

Coverage: 1 gallon size covers up to 600ft².

Drying Time: Allow to dry for a minimum of 4 hours between coats. Let dry for 24 hours before allowing light traffic, and one week for heavy traffic or to lay a rug. Wait 30 days for the varnish to fully cure before cleaning with water or cleaning products.

Cleaning: Clean tools with hot soapy water immediately after use.

VOC : < 250 g/L

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.

WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT



PREMIUM FLOOR GRADE FORMULA



EXCELLENT BUILD BETWEEN COATS



FAST DRYING



LOW ODOR

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.




WARNING: This product can expose you to chemicals, including NMethyl-2-pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN




WATERBASED TOP COAT

FLOOR GRADE

SATIN

1 gal



WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

Surface Preparation: Sand with #120 or #150 grit sandpaper. Do not use steel wool. Vacuum the dust and wipe with a clean, dry cloth.

For Use on Stain: Follow the manufacturer's instructions for applying the stain. Ensure that the surface is completely dry before applying the SAMAN TOP COAT.

For best results, use SAMAN stains.

Preparation of Already Varnished Surfaces: Surfaces must be dry, clean, and free of dust, mold, wax, grease, and moisture. Already varnished surfaces should be washed first with SAMAN TSP eco and lightly sanded with 150-grit sandpaper.

Mixing: Ensure that the product is at room temperature. Stir regularly with a stick during the application.

Application: Apply 2 to 3 even coats following the direction of the wood grain. Sand between each coat with 180-grit sandpaper. After sanding, vacuum the dust and wipe with a clean, damp cloth to remove all residues.

Recommended Applicators: High-quality brush, lint-free 6mm roller, HVLP spray gun.

Coverage: 1 gallon size covers up to 600ft².

Drying Time: Allow to dry for a minimum of 4 hours between coats. Let dry for 24 hours before allowing light traffic, and one week for heavy traffic or to lay a rug. Wait 30 days for the varnish to fully cure before cleaning with water or cleaning products.

Cleaning: Clean tools with hot soapy water immediately after use.

VOC : < 250 g/L

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.

WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT



PREMIUM FLOOR GRADE FORMULA



EXCELLENT BUILD BETWEEN COATS



FAST DRYING



LOW ODOR

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.




WARNING: This product can expose you to chemicals, including NMethyl-2-pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6




SAMAN



WATERBASED TOP COAT

FLOOR GRADE SEMI - GLOSS

1 gal



WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

Surface Preparation: Sand with #120 or #150 grit sandpaper. Do not use steel wool. Vacuum the dust and wipe with a clean, dry cloth.

For Use on Stain: Follow the manufacturer's instructions for applying the stain. Ensure that the surface is completely dry before applying the SAMAN TOP COAT.

For best results, use SAMAN stains.

Preparation of Already Varnished Surfaces: Surfaces must be dry, clean, and free of dust, mold, wax, grease, and moisture. Already varnished surfaces should be washed first with SAMAN TSP eco and lightly sanded with 150-grit sandpaper.

Mixing: Ensure that the product is at room temperature. Stir regularly with a stick during the application.

Application: Apply 2 to 3 even coats following the direction of the wood grain. Sand between each coat with 180-grit sandpaper. After sanding, vacuum the dust and wipe with a clean, damp cloth to remove all residues.

Recommended Applicators: High-quality brush, lint-free 6mm roller, HVLP spray gun.

Coverage: 1 gallon size covers up to 600ft².

Drying Time: Allow to dry for a minimum of 4 hours between coats. Let dry for 24 hours before allowing light traffic, and one week for heavy traffic or to lay a rug. Wait 30 days for the varnish to fully cure before cleaning with water or cleaning products.

Cleaning: Clean tools with hot soapy water immediately after use.

VOC : < 250 g/L

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.

WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT



PREMIUM FLOOR GRADE FORMULA



EXCELLENT BUILD BETWEEN COATS



FAST DRYING



LOW ODOR

FOR REMARKABLE AND DURABLE RESULTS

Avoid eye and skin contact.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Eye Contact: Flush eyes with water. Get medical attention if irritation persists. Skin Contact: Wash with soap and water. Get medical attention if irritation persists. Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious or drowsy person. Rinse mouth with water. Call a physician or Poison Center for advice.




WARNING: This product can expose you to chemicals, including NMethyl-2-pyrrolidone, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.p65warnings.ca.gov

Made in Canada

SAMAN

Victoriaville, Québec,
Canada G6T 0T6



SAMAN




WATERBASED TOP COAT

FLOOR GRADE

GLOSS

1 gal



WATERBASED TOP COAT

PREMIUM SERIES

IDEAL FOR EVERY INTERIOR PROJECT

Surface Preparation: Sand with #120 or #150 grit sandpaper. Do not use steel wool. Vacuum the dust and wipe with a clean, dry cloth.

For Use on Stain: Follow the manufacturer's instructions for applying the stain. Ensure that the surface is completely dry before applying the SAMAN TOP COAT.

For best results, use SAMAN stains.

Preparation of Already Varnished Surfaces: Surfaces must be dry, clean, and free of dust, mold, wax, grease, and moisture. Already varnished surfaces should be washed first with SAMAN TSP eco and lightly sanded with 150-grit sandpaper.

Mixing: Ensure that the product is at room temperature. Stir regularly with a stick during the application.

Application: Apply 2 to 3 even coats following the direction of the wood grain. Sand between each coat with 180-grit sandpaper. After sanding, vacuum the dust and wipe with a clean, damp cloth to remove all residues.

Recommended Applicators: High-quality brush, lint-free 6mm roller, HVLP spray gun.

Coverage: 1 gallon size covers up to 600ft².

Drying Time: Allow to dry for a minimum of 4 hours between coats. Let dry for 24 hours before allowing light traffic, and one week for heavy traffic or to lay a rug. Wait 30 days for the varnish to fully cure before cleaning with water or cleaning products.

Cleaning: Clean tools with hot soapy water immediately after use.

VOC : < 250 g/L

As the conditions under which the product is used are beyond our control, we can only guarantee that it fully complies with our quality standards, and the manufacturer's liability, if applicable, is limited to the purchase price of the product.

For any additional questions, please consult SAM, our conversational chatbot.



FINISH WITH STYLE.